

www.AtlasSpecialtyTrailers.com

AUTO HAULERS









Atlas auto haulers are known for solid construction. These rounded top trailers are framed with steel tubing with 3/8" plywood lining. Other features are:

- Frame: Steel tube main rails, 16" on center chassis, 102" wide, triple tube tongue (20' or longer), undercoated chassis, partial side and front posts, dust barrier/sealed sidewalls, welded safety chains w/clasps, formed steel rear header, vertical hat post front wall w/roof bow top & bottom plates, sand pad.
- Axle & Tire: Torflex axle, electric brakes w/breakaway box, E-Z lube hubs with grease caps, 15" white spoke wheels, premium radial tires, chromed steel center caps.
- Exterior: Seamless one-piece aluminum roofing, .080 mill finish extruded aluminum roof cove, 24" high aluminum tread plate stoneguard finished w/ trimlock, .030 smooth aluminum exterior available in a wide range of colors, .030 wrapped rear w/aluminum trim, color matching screws in white, black, red, gray & silver, 5" screw pattern, fiberglass radius front cap, aluminum fenders and skirts, DOT/CSA lighting, sealed clearance lights, rear tail lights mounted in cornerposts, injection molded license plate bracket w/light, 35" vapor barrier.
- Interior: 3/4" Advantech decking, 3/8" plywood wall liner, 4-5000# floor D-Rings, 4-12V dome lights, 2-nonpowered roof vents, 2-12V wall switches.
- Doors: Welded aluminum frame, tube steel frame side door rough openings, aluminum trimmed rough openings, double sealed 48" side door, 4000# rear ramp spring assist, camlock latches, holdbacks on all doors, safety spring chains for side door.

Trailers in photographs may show options available at additional cost.

SPECIFICATIONS

	Cargo / Utility A*820TA2	Cargo / Utility A*714TA2	Cargo / Utility A*612SA	Cargo / Utility A*58SA	Autohauler AA8524TA3	Race AR8520TA2	Race AR8524TA3	Race AR8528TA3
Over-all Length	24'	18'	16'	12'	28'	24'	28'	32'
Over-all Width	8'5"	8'1"	7'8"	6'8"		8'6"	8'6"	8'6"
Over-all Height	8'6"	7'11 3/4"	7'11 3/4"	6'8"		8'9"	8'9"	8'9"
Platform Height	20"	19"	18"	18"	20"	18"	19"	19"
Interior Height	6'8"	6'1"	6'1"	5'1"	6'8"	7'	7'	7'
Interior Overall Length	20'5"	14'5"	12'4"	8'4"	24'5"	19' 8"	23' 8"	27' 8"
Interior Width	7'8"	6'8"	5'8"	4'8"	8'1"	8'	8'	8'
Between Wheel Wells	6'10"	6'8"	NA	NA	6'9 1/2"	6'9"	6'9"	6'9"
Side Door	Optional	Optional	Optional	Optional	Standard	Standard	Standard	Standard
Side Door Width	32, 36, 48	32, 36	32, 36	24	48"	48"	48"	48"
Side Door Opening Height	5'11"	5'5"	5'3"	4'3"	72"	78 1/2"	78 1/2"	78 1/2"
Rear Door	Double	Double	Double	Double	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	5'11 1/2"	5'5 1/2"	5'5 1/2"	4'5 1/2"	75" ·	75" [·]	75"	75"
Rear Door Opening Width	7'1"	6'	4'11"	4'	89 1/4"	89 1/4"	89 1/4"	89 1/4"
Hitch Weight	300 lbs.	250 lbs.	165 lbs.	100 lbs.	420 lbs.	355 lbs.	420 lbs.	465 lbs.
Ball Size	2-5/16"	2-5/16"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
G.A.W.R.	7,000 lbs.	7,000 lbs.	3,500 lbs.	3,500 lbs.	10,400 lbs.	7,000 lbs.	10,400 lbs.	10,400 lbs.
G.V.W.R.	7,000 lbs.	7,000 lbs.	2,990 lbs.	2,990 lbs.	10,160 lbs.	7,000 lbs.	10,160 lbs.	10,160 lbs.
Curb Weight	2,850 lbs.	2,250 lbs.	1,390 lbs.	1,010 lbs.	4,200 lbs.	3,550 lbs.	4,200 lbs.	4,650 lbs.
Payload Capacity	4,150 lbs.	4,750 lbs.	1,600 lbs.	1,980 lbs.	5,960 lbs.	3,450 lbs.	5,960 lbs.	5,510 lbs.
Brakes	Electric	Electric	Optional	Optional	Electric	Electric	Electric	Electric
Tires	ST205/75R15	ST205/75R15	ST205/75R15	ST205/R15	ST225-75R15	ST205-75R15	ST225-75R15	ST225-75R15
Wheels	5 Bolt	5 Bolt	5 Bolt	5 Bolt		5 Bolt	6 Bolt	6 Bolt
Frame	6" Tube	6" Tube	3" Tube	3" Tube	6" Tube	6" Tube	6" Tube	8" Tube
Floor	3/4" Advantech	3/4" Advantech			3/4" Advantech		3/4" Advantech	3/4" Advantech
Floor Crossmember Loc.	24" O/C	24" O/C	24" O/C	24" O/C		16" O/C	16" O/C	16" 0/C
Cargo / Utility	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	White Vinyl	White Vinyl	White Vinyl
Wall Post Loc.	16" O/C	16" O/C	16" O/C	16" O/C	16" 0/C	16" O/C	16" O/C	16" O/C
Roof 24" O/C								

Model number of any particular unit does not necessarily reflect the overall length of the unit
All Illustrations and Specifications contained in this literature are based on the latest product information at time of publication

BUILT FOR STRENGTH, BUILT TO LAST

Atlas Specialty Trailers is a manufacturer of quality-built enclosed cargo trailers. Widths of 4', 5', 6', 7', 8', and 8.5' and lengths from 6' thru 40' are available. A wide variety of options are available, and every trailer comes with a full three (3) year limited structural warranty. All trailers are enclosed and manufactured in Elkhart, Indiana,

using steel frame construction,

3/8" plywood-lined interiors and colored aluminum exterior.
Atlas Specialty Trailers are competitively priced within the industry, and the fit & finish of each trailer is "THE FINEST THERE IS"!



AUTO • RACE • CARGO & UTILITY • SNOWMOBILE/SPORT • MOTORCYCLE • GOOSENECK & FIFTH WHEEL

Your Atlas Dealer is:

Rondo Enterprises, Inc ~ Truck & Trailer Sales
1115 E State St (PO Box 7)
Sycamore, IL 60178
815-899-4340, Fax 815-895-4237
www.rondotrailer.com