

LAMAR

— **DECKOVER TRAILERS** —



THE HASSLE-FREE TRAILER EXPERIENCE

THE **HASSLE-FREE** TRAILER EXPERIENCE



3 Year Structural Warranty

Lamar's warranty covers the primary frame for 3 years.

1 Year Component Warranty

Non wearing components are covered for 1 year.

Premium 3rd Party Component Warranty

Lamar uses high quality brands for parts and the warranty is covered by the parts respective manufacturer.

DECKOVER TRAILER

14,000 LB. GVWR

MODEL: F8



GVWR: 14,000 lbs.

Weight : 3,300 - 4,300 lbs.

Payload: 10,500 lbs.

Lengths: 16' - 24'

Widths: 102"

Frame: 8" 10 lb. I-Beam

Floor: Treated Pine

Deck Height: 34"

Loading Angle: 20°

Pull this trailer behind your $\frac{3}{4}$ ton. Perfect for equipment, bulk material, and pallets—the F8 offers generous space and a 14K GVWR. Great for agriculture and job site delivery.



F827

STANDARD FEATURES

Axles: 7K EZ Lube Elec Brake Spring Axles

Coupler: 2 5/16" 21K Demco Adj Coupler

Crossmembers: 16" Center-to-Center

Dove: Straight Deck

Floor: Treated Pine

Frame: 8" 10 lb. I-Beam

Hitch: Bumper Pull

Jack: Single 10K Drop-Leg Jack

Ramps: Pair of Slide In Ramps

Tie Downs: Standard Stake Pockets

Tires: 235/80 R16 (E) 10Ply

Toolbox: Expanded Metal Tool Tray

POPULAR UPGRADES

- SPARE TIRE MOUNT
- FRONT TOOLBOX
- 5' DOVE/RHINO RAMPS
- WELD ON D-RINGS
- 4' DOVE & 24" STAND UPS



DECKOVER TRAILER

14,000 - 21,000 LB. GVWR

MODEL: FS



GVWR: 14,000 - 21,000 lbs. **Lengths:** 18' - 40'
Weight : 5,000 - 8,000 lbs. **Widths:** 102"
Payload: 9,000 - 15,000 lbs. **Frame:** 12" I-Beam

Floor: Treated Pine
Deck Height: 36"
Loading Angle: 21°

The FS easily handles wider equipment and bulk material. Popular for farm use, we recommend at least a ¾ ton truck to haul this smooth-pulling trailer. 1-ton on the 21k is advised.



FS37

STANDARD FEATURES

Axles: 7K | 8K EZ Lube Elec Brake Spring Axles

Coupler: 2 5/16" 25K Gooseneck Coupler

Crossmembers: 16" Center-to-Center

Dove: Straight Deck

Floor: Treated Pine

Frame: 12" I-Beam (14lb. - 19 lb.)

Hitch: Gooseneck

Jack: Dual 10K Drop Leg Jack

Ramps: Pair of Slide In Ramps

Spare: Spire Tire

Toolbox: Front Tool Box

Tie Downs: Standard Stake Pockets

Tires: 235/80 R16 (E) 10Ply | 215/75 R17.5 (H) 16Ply SS

POPULAR UPGRADES

- 5' DOVE/RHINO RAMPS
- 14 PLY TIRES
- WINCH PLATE
- LOW PROFILE FRAME
- SLIDING STRAP WINCH TRACK



DECKOVER TRAILER

20,000 - 30,000 LB. GVWR

MODEL: FD & FG



GVWR: 20,000 - 30,000 lbs.

Weight : 6,000 - 11,000 lbs.

Payload: 12,000 - 21,000 lbs.

Lengths: 25' - 40'

Widths: 102"

Frame: 12" I-Beam

Floor: Treated Pine

Deck Height: FG 38" | FD 37"

Loading Angle: 22°

Need to move heavy equipment or material with your 1-ton truck? The FD gives you up to a 24K GVWR with a tough 12" 19lb frame to match. Hot shotters love the 24k.

When you're hauling heavy machinery or equipment with your 1 ton, the FG is the trailer to trust. Its massive 30K GVWR and 12" 22lb frame hold up to the heaviest work.



FD2A/FD2B/FG2C



FG3A

STANDARD FEATURES

Axles: 10K | 12K | 15K Elec Brake Spring Axles

Coupler: 2 5/16" 25K | 2 5/16" 30K Gooseneck Coupler

Crossmembers: 16" Center-to-Center

Dove: Straight Deck

Frame: 12" I-Beam (19 lb. - 22 lb.)

Floor: Treated Pine

Hitch: Gooseneck

Jack: Dual 10K Drop-Leg Jack

Ramps: Pair of Slide In Ramps

Spare: Spare Tire

Tie Downs: Standard Stake Pockets

Tires: 235/80 R16 (E) 10Ply Tire Dual Wheel

215/75 R17.5 (H) 16 Ply Tire Dual Wheel

Toolbox: Front Tool Box

POPULAR UPGRADES

- LOW PROFILE PIERCED BEAM
- 5' DOVE/RHINO RAMPS
- DUAL WHEELS
- WINCH MOUNT
- 4' SIDE TOOLBOX



DECKOVER TRAILER

14,000 - 21,000 LB. GVWR

MODEL: FA



GVWR: 14,000 - 21,000 lbs.

Weight : 5,500 - 6,000 lbs.

Payload: 8,000 - 14,500 lbs.

Lengths: 24' - 26'

Widths: 102"

Frame: 10" 12 lb. I-Beam

Floor: Treated Pine

Deck Height: 34"

Loading Angle: 15°

The FA's full-width tilt deck is perfect for hauling equipment like tractors and skid steers with a ¾ ton tow vehicle. Easy to load—no ramps needed.



FA27/FA28



FA37

STANDARD FEATURES

Axles: 7K EZ Lube Elec Brake | 8K Elec Brake Oil Bath

Coupler: 2 5/16" 25K Gooseneck Coupler

Crossmembers: 16" Center-to-Center

Floor: Treated Pine

Frame: 10" 12 lb. I-Beam

Hitch: Gooseneck

Jack: Dual 10K Drop-Leg Jacks

Spare: Spare Tire

Tie Downs: Standard Stake Pockets

Tires: 235/80 R16 (E) 10Ply | 215/75 R17.5 (H) 16Ply SS

Toolbox: Front Toolbox

POPULAR UPGRADES

- WINCH PLATE
- BUMPERPULL HITCH
- 14 PLY TIRES
- 16 PLY SUPER SINGLE TIRES
- HYDRAULIC JACKS





HONOR **GOD**



SERVE **HUMBLY**



KEEP IT **SIMPLE**

903-782-9333 | info@lamartrailers.com
7271 FM 38 N. Sumner, Texas 75486



L A M A R T R A I L E R S . C O M